

L183.5 · TRACK SYSTEM

TRACK

IP20

MODEL CODE EL - 07.007A06000

**10 W**

LIGHT SOURCE

**950 lm**

LUMINANCE

**≥90**

CRI

**18°/23°/35°**

BEAM ANGLE

**-25~50°C**

OPERATING

02 — SPECIFICATIONS

Technical specifications

HOUSING	Aluminium body; black finish.
LED TYPE	SMD; CCT 2700K/3000K/3500K/4000K or 2700–6000K tunable (per order); CRI ≥90; SDCM <3.
BEAM ANGLE	18° / 23° / 35° optics available (per order).
LIGHT DISTRIBUTION	Direct.
ADJUSTABILITY	90° tilting.
OPERATING TEMP.	-25°C ~ 50°C.
DIMMING	Non-dim, 0/1–10V, DALI-2, Bluetooth, or ZigBee (per order).

ORDERING KEY

GF1010

Series — Track light

07.007A06000

Configuration — 10W, black

MODEL — EL-07.007A06000

Dimensions	L183.5 × H122mm; Head W117×D23mm	Input voltage	DC48V
Frequency	50 / 60 Hz	Rated life	35,000–50,000 h
Ingress protection	IP20		

MOUNTING & INSTALLATION

- 01** Align adapter

Align the track adapter with the rail at the loading angle.
- 02** Twist & lock

Rotate the fixture to engage the track contacts and lock in place.
- 03** Power on

Energise the circuit; select the dimming protocol as required.
- 04** Aim

Tilt up to 90° to the desired direction.

DALI-2

0/1-10V

BLUETOOTH

ZIGBEE

IP20

RoHS

CE