

SPIKE

IK 06

MODEL CODE EL - B3TNS0126



1× 6 W

LIGHT SOURCE



740 lm

LUMINANCE



IK 06

IMPACT



28°

BEAM ANGLE



-20~40°C

OPERATING

02 — SPECIFICATIONS

Technical specifications.

HOUSING	ADC-12 die-cast aluminium, powder coated T=60–80µm; ISO class 1 / ASTM 4B adhesion.
LIGHT WINDOW	Tempered glass, T=4mm.
LENS	OPTICS lens, efficiency ≥85%; 28° beam angle (B51).
LED TYPE / DRIVER	1× 6W COB; built-in on/off driver.
CABLE GLAND	Nickel-coated copper.
GASKET	Waterproof silicone gasket.
OPERATING TEMP.	-20°C ~ 40°C.
POWER CABLE	H05RN-F 2×1.0mm², L=2.0m (24V) · H05RN-F 3×1.0mm², L=2.0m (120/240V) — outside luminaire.

ORDERING KEY

B3TN

Series — Spikelight

S0126

Configuration — 1×6W COB spot

MODEL — EL-B3TNS0126

Dimensions	—	Input voltage	DC24 / AC120 / AC240
Current	325 / 56 / 35 mA	Consumption	7.8 / 6.7 / 7.2 W
IK rating	06		

MOUNTING & INSTALLATION

01

Mark & site

Choose the planting position and clear the ground.

02

Insert spike

Push the ground spike fully into the soil.

03

Connect & seal

Wire the supply through the gasketed gland.

04

Aim & lock

Set pan/tilt to the desired beam direction and lock the pivot.

ON / OFF

COB LED

DIE-CAST

SEALED

IK 06

RoHS

CE