

LINEAR GRAZER SERIES

LINEAR GRAZER

IP-67

MODEL CODE EL - B6JD1834



18× 0.7 W

LIGHT SOURCE



900 lm

LUMINANCE



IK 05

IMPACT



IP-67

SEALING



-20~40°C

OPERATING

02 — SPECIFICATIONS

Technical specifications

HOUSING	ADC-12 die-cast aluminium, powder coated T=60–80µm. IP-67 sealed, ISO class 1 / ASTM 4B adhesion.
LIGHT WINDOW	Vitop fire-retardant PC diffuser, T=3mm — single continuous linear window.
LED TYPE / DRIVER	18× 0.7W SMD; built-in constant-current driver, DC24V.
POWER CABLE	H05RN-F 2×0.75mm² (DC24V), L=0.3m.
BASE	End-mount brackets with adjustable tilt, surface or recessed fixing.
DIMMING	Triac & PWM standard; 1–10V and DALI customised.
OPERATING TEMP.	-20°C ~ 40°C.
FINISH	Dark Grey (primary) · Silver Grey · Sanded Black — powder coat.

ORDERING KEY

B6JD

Series — Linear Grazer wall washer

1834

Configuration — 18×0.7W single-face engine

MODEL — EL-B6JD1834

Dimensions	Surface bar	Input voltage	DC24V
Current	525 mA	Consumption	12.6 W
IK rating	05		

MOUNTING & INSTALLATION

01

Mark & drill

Position the end brackets; drill and plug fixing points.

02

Fix the plate

Secure brackets to wall, façade, or ground recess.

03

Connect & seal

Wire the supply through the gasketed gland.

04

Adjust & lock

Set beam tilt, seat the bar in the brackets, and lock.

TRIAC

PWM

1-10V

DALI

IP-67

RoHS

CE