

L303 TRACK SYSTEM

TRACK

IP20

MODEL CODE EL - 07.022A03000

**10 W**

LIGHT SOURCE

**950 lm**

LUMINANCE

**≥90**

CRI

**110°**

BEAM ANGLE

**-25~50°C**

OPERATING

02 — SPECIFICATIONS

Technical specifications

HOUSING	Aluminium body; black finish.
LED TYPE	SMD; CCT 3000K/4000K/6000K or 3000–6000K tunable (per order); CRI ≥90; SDCM <3.
BEAM ANGLE	110° linear diffuser.
LIGHT DISTRIBUTION	Direct.
ADJUSTABILITY	None (fixed, flush-mounted).
OPERATING TEMP.	-25°C ~ 50°C.
DIMMING	Non-dim, 0/1–10V, DALI-2, Bluetooth, or ZigBee (per order).

ORDERING KEY

SG0010

Series — Track light

07.022A03000

Configuration — 10W, black

MODEL — EL-07.022A03000

Dimensions	L303 × H43 × D23mm	Input voltage	DC48V
Frequency	50 / 60 Hz	Rated life	35,000–50,000 h
Ingress protection	IP20		

MOUNTING & INSTALLATION

01 Align adapter

Align the track adapter with the rail at the loading angle.

02 Twist & lock

Rotate the fixture to engage the track contacts and lock in place.

03 Power on

Energise the circuit; select the dimming protocol as required.

04 Secure

Confirm the bar sits flush and parallel to the track.

DALI-2

0/1-10V

BLUETOOTH

ZIGBEE

IP20

RoHS

CE