

Ø25 · TRACK SYSTEM

TRACK

IP20

MODEL CODE EL - 07.008A01000

**3 W**

LIGHT SOURCE

**180 lm**

LUMINANCE

**≥90**

CRI

**20°/26°/36°/50°**

BEAM ANGLE

**-25~50°C**

OPERATING

02 — SPECIFICATIONS

Technical specifications

HOUSING	Aluminium body; black finish.
LED TYPE	SMD; CCT 2700K/3000K/3500K/4000K (per order); CRI ≥90; SDCM <3.
BEAM ANGLE	20° / 26° / 36° / 50° optics available (per order).
LIGHT DISTRIBUTION	Direct.
ADJUSTABILITY	365° rotation; 90° tilting.
OPERATING TEMP.	-25°C ~ 50°C.
DIMMING	Non-dim, 0/1–10V, DALI, Bluetooth, or ZigBee (per order).

ORDERING KEY

IT2003

Series — Track light

07.008A01000

Configuration — 3W, black

MODEL — EL-07.008A01000

Dimensions	Rail L183.5×H18mm; Head Ø25×50mm	Input voltage	AC220–240V
Frequency	50 / 60 Hz	Rated life	35,000–50,000 h
Ingress protection	IP20		

MOUNTING & INSTALLATION

01 Align adapter

Align the track adapter with the rail at the loading angle.

02 Twist & lock

Rotate the fixture to engage the track contacts and lock in place.

03 Power on

Energise the circuit; select the dimming protocol as required.

04 Aim

Rotate up to 365° and tilt up to 90° to the desired direction.

DALI

0/1-10V

BLUETOOTH

ZIGBEE

IP20

RoHS

CE