

LINEAR GRAZER SERIES

LINEAR GRAZER

IP-67

MODEL CODE EL - B6JD4234



42× 0.7 W

LIGHT SOURCE



2400 lm

LUMINANCE



IK 05

IMPACT



IP-67

SEALING



-20~40°C

OPERATING

02 — SPECIFICATIONS

Technical specifications.

HOUSING	Extruded aluminum anodized finishing
LIGHT WINDOW	Tempered glass. T=3mm
LED TYPE	42× 0.7W SMD
POWER CABLE	Outside of luminaire H07RN-F 2×1.5mm², L=1.2m (24V)
BRACKET	H05RN-F 3×1.0mm², L=0.5m (240V) Aluminum anodized finishing
DIMMING	Triac PWM 1-10V Dali (24V)
OPERATING TEMP.	-20°C ~ 40°C
GASKET / LENS	Glass and housing are silicone sealed OPTICS lens, efficiency ≥85%

ORDERING KEY

B6JD
Series — Linear Grazer wall washer

4234
Configuration — 42×0.7W single-face engine

MODEL — EL-B6JD4234

Dimensions	L=1200 mm	Input voltage	DC24V / AC240V
Current	24V=1458 mA 240V=186 mA	Consumption	24V=35 W 240V=41 W
IK rating	05		

MOUNTING & INSTALLATION

01

Mark & drill

Position the end brackets; drill and plug fixing points.

02

Fix the plate

Secure brackets to wall, façade, or ground recess.

03

Connect & seal

Wire the supply through the gasketed gland.

04

Adjust & lock

Set beam tilt, seat the bar in the brackets, and lock.

TRIAC

PWM

1-10V

DALI

IP-67

RoHS

CE