

Ø420 · FLOOD

FLOODLIGHT

IK 06

MODEL CODE EL - C240C

**240 W**

LIGHT SOURCE

**19200 lm**

LUMINANCE

**IK 06**

IMPACT

**4.5–80°**

BEAM ANGLE

**-35~60°C**

OPERATING

02 — SPECIFICATIONS

Technical specifications

HOUSING	Die-cast aluminium ADC12, powder coating finish.
COVER	Toughened glass.
LED TYPE	SMD; CREE / NICHIA / OSRAM / LUMILEDS / EPISTAR (per order).
BEAM ANGLE	4.5° / 8° / 15° / 30° / 40° / 60° / 80° / 30°×60° optics available.
CONTROL	DMX512 / ON-OFF.
SEALING	IP66; IK06 impact rated; Protection Class I.
OPERATING TEMP.	-35°C ~ 60°C (storage -40°C ~ 70°C).
INPUT VOLTAGE	AC220V; lifespan >50,000 hrs (Ta=35°C @ L70).

MODEL — EL-C240C

Dimensions	Ø420 / H499mm	Input voltage	AC220V
Current	—	Consumption	240 W
IK rating	06		

MOUNTING & INSTALLATION

- 01

Mark & drill

Position the mounting bracket; drill and plug fixing points.
- 02

Fix the bracket

Secure bracket to wall, ceiling, or surface.
- 03

Connect & seal

Wire the supply through the gasketed gland.
- 04

Aim & lock

Set pan/tilt to the desired beam direction and lock the pivot.

DMX512

ON / OFF

IP66

>50K HRS

IK 06

RoHS

CE