

EUROLITE


OUTDOOR BOLLARD

Ø110 · H800 · FLANGE BASE

OUTDOOR BOLLARD

IK 07

MODEL CODE EL - D9AFH1234



12× 0.5 W

LIGHT SOURCE



450 lm

LUMINANCE



IK 07

IMPACT



IP66

IP RATING



-20~40°C

OPERATING

02 — SPECIFICATIONS

Technical specifications

HOUSING	12# die-cast aluminium, RAL9005 powder coated, T=60–80µm; ISO class 1 / ASTM class 4B adhesion.
BASE	Flange base, Ø150; non-detachable, M12 anchor bolts.
LIGHT WINDOW	PMMA diffuser window.
LIGHT ENGINE	IP66 modular light-source unit with PC cover; IP66 built-in power module.
LED TYPE / DRIVER	12× 0.5W SMD; built-in on/off driver.
SEALING	IP67 cable gland.
OPERATING TEMP.	-20°C ~ 40°C.
POWER CABLE	H05RN-F 2×1.0mm², L=0.5m (24V) · H05RN-F 3×1.0mm², L=0.5m (120/240V) — outside luminaire, without waterstopper.

ORDERING KEY

D9AFH

Series — Outdoor bollard light

1234

Configuration — 12×0.5W, flange base

MODEL — EL-D9AFH1234

Dimensions	Ø110 / H800mm	Input voltage	DC24 / AC120 / AC240
Current	250 / 60 / 35 mA	Consumption	6 / 7 / 7 W
IK rating	07		

MOUNTING & INSTALLATION

01 Set anchor bolts

Position the flange template and set M12 anchor bolts in the foundation.

02 Route cable

Run the supply cable up through the base and pot the entry.

03 Connect & seal

Wire the supply through the gasketed cable gland.

04 Fit & secure

Lower the bollard onto the anchor bolts and torque the base nuts evenly.

TRIAC

0–10V

DALI (EXT.)

IP66

IK 07

RoHS

CE