

LINEAR GRAZER SERIES

LINEAR GRAZER

IP-67

MODEL CODE EL - B6KD4257



42× 1.3 W

LIGHT SOURCE



4750 lm

LUMINANCE



IK 05

IMPACT



IP-67

SEALING



-20~40°C

OPERATING

02 — SPECIFICATIONS

Technical specifications.

HOUSING	Extruded aluminum anodized finishing
LIGHT WINDOW	Tempered glass. T=4mm
LED TYPE	42× 1.3W SMD
POWER CABLE	Outside: H07RN-F 2×1.5mm², L=1.5m (24V) H05RN-F 3×1.0mm², L=0.3m (240V)
BRACKET	Aluminum anodized finishing
DIMMING	Triac PWM 1-10V Dali (24V)
OPERATING TEMP.	-20°C ~ 40°C
GASKET / LENS	Glass and housing are silicone sealed OPTICS lens, efficiency ≥85%

ORDERING KEY

B6KD Linear Grazer	4257 42×1.3W Single-Face
-----------------------	-----------------------------

MODEL — EL-B6KD4257

Dimensions	L=1132 mm	Input voltage	DC24V / AC240V
Current	24V=2603 mA 240V=317 mA	Consumption	24V=62 W 240V=70 W
IK rating	05		

MOUNTING & INSTALLATION

01 Mark & drill	02 Fix the plate
Position the end brackets; drill and plug fixing points.	Secure brackets to wall, façade, or ground recess.
03 Connect & seal	04 Adjust & lock
Wire the supply through the gasketed gland.	Set beam tilt, seat the bar in the brackets, and lock.

TRIAC	PWM	1-10V	DALI	IP-67	RoHS	CE
-------	-----	-------	------	-------	------	----